



12V XR

Offering Extreme runtime, the 12V XR range offers great performance combined with a lighter design.

www.DEWALT.co.uk

12V XR SUB-COMPACT DRILL DRIVER

DCD701D2


Length	152mm
No Load Speed	0-425 / 0-1500rpm
Max. Torque	57.5Nm
Max. Drilling Capacity Wood	20mm
Max. Drilling Capacity Metal	10mm



12V XR COMPACT DRILL DRIVER

DCD710D2


No Load Speed	0 - 400/1500rpm
Max. Torque	24Nm
Max. Drilling Capacity Wood	20mm
Max. Drilling Capacity Metal	10mm



12V XR COMPACT HAMMER DRILL DRIVER

DCD716D2

No Load Speed	0-400/1500rpm
Max. Torque	30Nm
Beats Per Minute	0-6000/22500bpm
Max. Drilling Capacity Wood	20mm
Max. Drilling Capacity Metal	10mm
Max. Drilling Capacity Masonry	8mm



12V XR SUB-COMPACT IMPACT DRIVER

DCF801D2

No Load Speed	0 - 950 / 0 - 1950 / 0 - 2850rpm
Max. Torque	163Nm
Impacts Per Minute	3600ipm
Bit Holder	1/4" (6.35mm)
Max. Bolt Diameter	M10



12V XR COMPACT IMPACT DRIVER

DCF815D2


No Load Speed	0 - 2450rpm
Max. Torque	107Nm
Impacts Per Minute	0 - 3400ipm
Bit Holder	1/4" (6.35mm)
Max. Bolt Diameter	M10



12V XR SUB-COMPACT 3/8" IMPACT WRENCH

DCF902D2

No Load Speed	0 - 2850 / 0 - 1000 / 0 - 2850rpm
Max. Torque	168Nm
Impacts Per Minute	0 - 3600ipm
Bit Holder	3/8" (9.525mm)
Max. Bolt Diameter	M14



12V XR COMPACT WRENCH

DCF813D2


No Load Speed	0 - 2450rpm
Max. Torque	130Nm
Impacts Per Minute	0 - 3400ipm
Bit Holder	3/8" (9.525mm) Hog Ring
Max. Bolt Diameter	M12



12V XR SUB-COMPACT SCREWDRIVER

DCF601D2

No Load Speed	0 - 1100rpm
Max. Torque	8Nm
Bit Holder	1/4" (6.35mm)



12V XR SCREWDRIVER

DCF610D2

No Load Speed	0 - 1050rpm
Max. Torque	8Nm
Bit Holder	1/4" (6.35mm)



12V XR COMPACT RECIPROCATING SAW

DCS310D2

No Load Stroke Rate	0 - 2700spm
Stroke Length	14mm
Hand and Arm Vibration - cutting boards	8.5m/s ²



12V XR INSPECTION CAMERA

DCT410D1

Cable Size	900 x 17mm
Waterproof Cable	Yes
Wireless Screen	Yes
Zoom	3x
Data Storage	Micro SD Card
Resolution	320 x 480 dpi



DCT410N - BARE UNIT

12V XR INFRARED THERMOMETER

DCT414N

Temperature Range	-30°C to 550°C
Screen Size	36mm
Adjustable Emissivity	0.1 to 1.0
Field of view	30cm x 2.5cm
Data Storage	Micro SD card
LED Indicator	Yes



BARE UNIT

12V XR SUB-COMPACT TWIN PACK

DCK2110L2T



- Kit Includes:
 DCD701 12V XR Brushless Sub-Compact Drill Driver
 DCF801 12V XR Brushless Sub-Compact Impact Driver
 DCB124 2x3Ah Batteries
 DCB115 Multi Voltage Charger
 TSTAK™ II Kitbox



12V XR COMPACT TWIN KIT

DCK218D2T



- Kit Includes:
 DCD716 Hammer Drill Driver
 DCF815 Impact Driver
 2 x DCB127 2Ah Batteries
 DCB113 Multi Voltage Charger
 TSTAK™ II Kitbox



12V XR TWIN KIT

DCK211D2T



- Kit Includes:
 DCD710 Drill Driver
 DCF815 Impact Driver
 DCB127 2 x 2Ah Batteries
 DCB113 Multi Voltage Charger
 TSTAK™ V Clear Lid Organiser



12V XR COMPACT LED TORCH

DCL510N



Output	130 Lumens
Size	123mm x 52mm



BARE UNIT

12V XR 3AH BATTERY

DCB124-XJ



Voltage	12V
Battery Capacity	3Ah

