

XR

18V

**MORE CAPACITY.
MORE RUNTIME.
SAME SIZE.**

The XR Li-Ion range offers EXTREME runtime, increased efficiency and improved performance. The intelligent switch module combined with improved brushless technology helps to increase lifetime of both tool and battery. 18V XR batteries meet all users' needs - from ergonomic design (2Ah) to higher capacity (5Ah).

www.DEWALT.co.uk

18V XR TOOL CONNECT

GET CONNECTED. TAKE CONTROL.

Save time and money with Tool Connect. Using the intelligent inventory management platform you will easily maximise your productivity and protect your investment.

Manage and track all your assets with the Bluetooth enabled tag or by connecting the 18V XR battery connector to your existing 18V XR tools. With the new smart 18V tools, you can also customise the tools specifications for the perfect performance.

Take complete control of your own assets, or those of your team, via the Tool Connect App or web platform, and get ready for the jobsite of the future.



18V XR BATTERY

DCB184B



Android Compatible	Yes
iOS Compatible	Yes
Tool Connect Compatible	Yes



18V XR BATTERY

DCB183B



Android Compatible	Yes
iOS Compatible	Yes
Tool Connect Compatible	Yes



18V XR COMPACT HAMMER DRILL DRIVER WITH 2 X 2.0AH BATTERIES

DCD797D2B



Max. Torque	70Nm
No Load Speed	0 - 550/2000rpm
Beats Per Minute	0 - 9350/34000
Max. Drilling Capacity Wood	40mm
Max. Drilling Capacity Metal	13mm
Max. Drilling Capacity Masonry	13mm



18V XR XRP 3 SPEED PREMIUM COMBI DRILL

DCD997P2B



Max. Torque	95Nm
No Load Speed	0 - 450/1300/2000rpm
No Load Speed (Hammer)	0 - 500/1500/2250
Beats Per Minute	0 - 8600/25500/38250bpm
Max. Drilling Capacity Wood	55mm
Max. Drilling Capacity Metal	15mm
Max. Drilling Capacity Masonry	13mm



**18V XR COMPACT HAMMER DRILL +
IMPACT DRIVER + 2 X 5.0AH BATTERIES COMBI DRILL**

DCK2500P2B

Kit Includes:

- DCD797 Tool Connect Compact Brushless Hammer Drill
- DCF888 Tool Connect Brushless Impact Driver
- DCB184B 2 x 5.0 Ah Tool Connect Batteries
- DS150 Toughsystem™ Kitbox
- DCB115 240V Charger



18V XR IMPACT DRIVER 2AH

DCF888D2B

Max. Torque	205Nm
No Load Speed	0 - 1000/2800/3250rpm
Impacts Per Minute	0 - 3800ipm
Bit Holder	1/4" (6.35mm)
Max. Bolt Diameter	M12



18V XR CONNECTOR

DCE040

IP Rating	IP68
DCE041K4	4 pack
DCE041K10	10 pack
DCE041K10-XJ	Tool Connect Tag 10 pack
DCE041K4-XJ	Tool Connect Tag 4 pack



18V XR XRP 3 SPEED PREMIUM COMBI DRILL

DCD996P2

Max. Torque	95Nm
No Load Speed	0 - 450/1300/2000rpm
No Load Speed (Hammer)	0 - 500/1500/2250rpm
Beats Per Minute	0 - 8600/25500/38250bpm
Max. Drilling Capacity Wood	55mm
Max. Drilling Capacity Metal	15mm
Max. Drilling Capacity Masonry	13mm




DCD997P2B-GB - 5AH TOOLCONNECT BLUETOOTH BATTERIES

18V XR XRP 3 SPEED COMBI DRILL

DCD985M2

Max. Torque	80Nm
No Load Speed	0 - 575/1350/2000rpm
Beats Per Minute	9775/22900bpm
Max. Drilling Capacity Wood	50mm
Max. Drilling Capacity Metal	13mm
Max. Drilling Capacity Masonry	16mm



18V XR 2 SPEED COMPACT COMBI DRILL

DCD796P2

Max. Torque	70Nm
No Load Speed	0 - 550/2000rpm
Beats Per Minute	0 - 9350/34000bpm
Max. Drilling Capacity Wood	40mm
Max. Drilling Capacity Metal	13mm
Max. Drilling Capacity Masonry	13mm




DCD796D2 - 2AH BATTERIES DCD797D2B - 2AH TOOLCONNECT BLUETOOTH BATTERIES

18V XR XRP 3 SPEED PREMIUM DRILL DRIVER

DCD991P2


Max. Torque	95Nm
No Load Speed	0 - 450/1300/2000rpm
No Load Speed (Hammer Mode)	0 - 500/1500/2250rpm
Max. Drilling Capacity Wood	55mm
Max. Drilling Capacity Metal	15mm



18V XR 2 SPEED COMPACT DRILL DRIVER

DCD791P2

Max. Torque	70Nm
No Load Speed	0 - 550/2000rpm
Max. Drilling Capacity Wood	40mm
Max. Drilling Capacity Metal	13mm



18V XR 3 SPEED IMPACT DRIVER

DCF887P2

Max. Torque	205Nm
No Load Speed	0 - 1000/2800/3250rpm
Impacts Per Minute	0 - 3800ipm
Bit Holder	1/4" (6.35mm)
Max. Bolt Diameter	M12



DCF887D2 - 2AH BATTERIES DCF887N - BARE UNIT

18V XR COMPACT IMPACT WRENCH

DCF880M2

Max. Torque	203Nm
No Load Speed	0 - 2300rpm
Impacts Per Minute	0 - 2700ipm
Bit Holder	1/2" (13mm)
Max. Bolt Diameter	M16




DCF880N - BARE UNIT

18V XR 1/2" COMPACT HIGH TORQUE WRENCH

DCF894P2

Max. Torque	447Nm
No Load speed	0-900/0-2000rpm
Impacts Per Minute	3100ipm
Hand/Arm Vibration	13.5m/s ²
Power Output	580W
Bit Holder	1/2" (13mm)
PRECISION WRENCH™	Yes



DCF894N - BARE UNIT

18V XR 3 SPEED HIGH TORQUE IMPACT WRENCH

DCF899P2

Max. Torque	135/400/950Nm
No Load Speed	0 - 400/1200/1900rpm
Impacts Per Minute	0 - 2400ipm
Bit Holder	1/2" (12.7mm)
Max. Bolt Diameter	M20
Power Output	610W



DCF899N - BARE UNIT DCF899HN - BARE UNIT HOG RING

18V XR BRUSHLESS 3/4" HIGH TORQUE IMPACT WRENCH

DCF897N

Max. Torque	950Nm
No Load Speed	0-1900rpm
Impacts Per Minute	0-2400ipm
Bit Holder	3/4" (19.05mm)
Power Output	610W




18V XR COLLATED SCREWDRIVER

DCF620P2K

Max. Torque	5 - 30Nm
No Load Speed	0 - 4400rpm
Bit Holder	1/4" (6.35mm)
Power Output	435W



DCF6201 Collated Screw Magazine included in kit versions only.



DCF620D2K - 2AH BATTERIES DCF620N - BARE UNIT DCF6201 - COLLATED MECHANISM

18V XR SELF DRILLING SCREWDRIVER

DCF622P2

Max. Torque	34Nm
No Load Speed	0 - 2000rpm
Bit Holder	1/4" (6.35mm)
Max. Screw Length	6.0mm
Power Output	850W



DCF622N - BARE UNIT

18V XR RIGHT ANGLE DRILL

DCD740C1

Max. Torque	33Nm
No Load Speed	0 - 650/2000rpm
Max. Drilling Capacity Wood	28mm
Max. Drilling Capacity Metal	10mm




DCD740N - BARE UNIT

18V XR 24MM 2KG SDS-PLUS 3-MODE HAMMER

DCH283P2

No Load Speed	0 - 980rpm
Blows Per Minute	0 - 4480bpm
Max. Drilling Capacity Concrete	26mm
Max. Drilling Capacity Metal	13mm
Max. Drilling Capacity Wood	30mm
Impact Energy	2.8J
Hand/Arm Vibration	8.5m/s ²




DCH283N - BARE UNIT

18V XR SDS PLUS 3-MODE HAMMER DRILL

DCH273P2

No Load Speed	0 - 1100rpm
Blows Per Minute	0 - 4600bpm
Max. Drilling Capacity Concrete	24mm
Max. Drilling Capacity Steel	13mm
Max. Drilling Capacity Wood	26mm
Impact Energy	2.1J
Hand/Arm Vibration	6.6m/s ²




DCH273N - BARE UNIT DCH274P2 - INCLUDES QUICK CHANGE CHUCK

18V XR SDS PLUS 3-MODE HAMMER DRILL

DCH253M2

No Load Speed	0 - 1200rpm
Blows Per Minute	0 - 4500bpm
Max. Drilling Capacity Concrete	24mm
Max. Drilling Capacity Steel	13mm
Max. Drilling Capacity Wood	26mm
Impact Energy	2.1J
Hand/Arm Vibration	6.6m/s ²



DCH253N - BARE UNIT DCH254M2 - INCLUDES QUICK CHANGE CHUCK

18V XR 125MM ANGLE GRINDER

DCG405P2

No Load Speed	9000rpm
Max. Disc Diameter	125mm
Spindle Thread	M14
Hand/Arm Vibration	4.4m/s ²



DCG405N - BARE UNIT DCG405FN - BARE UNIT FLATHEAD

18V XR 125MM ANGLE GRINDER

DCG412M2

No Load Speed	7000rpm
Max. Disc Diameter	125mm
Spindle Thread	M14
Hand/Arm Vibration	6.0m/s ²



DCG412N - BARE UNIT

18V XR BRUSHLESS DIE GRINDER

DCG426P2



Power Output	760 Watt
No Load Speed	0 - 10000/17500/25000
Max. Disc Diameter	38mm
Collet Size	6mm
Hand/Arm Vibration - Grinding	4.4m/s ²



DCG426N - NAKED UNIT

18V XR CONCRETE NAILER

DCN890P2



Nail Diameter	2.6-3.7mm
Magazine Angle	15°
Nail Length	13 - 57mm
Firing Mode	Rapid Cycle™ and Sequential



DCN890N - BARE UNIT

18V XR CONCRETE NAILER ATTACHMENTS

DCN8901-XJ	Driver Blade Replacement Kit for DCN890
DCN8902-XJ	Magnetic Contact Trip for DCN890
DCN8903-XJ	Non-Magnetic Contact Trip for DCN890
DCN8904-XJ	Drywall Contact Trip for DCN890
DCN8905-XJ	Extension Pole for DCN890



DCN8901-XJ

DCN8902-XJ



DCN8903-XJ

DCN8904-XJ

DCN8905-XJ



DCN890N - BARE UNIT

18V XR FRAMING NAILER

DCN692P2



Nail Diameter	2.8-3.3mm
Magazine Angle	30 - 34°
Nail Length	50 - 90mm
Firing Mode	Bump & Sequential
Temperature Range	-20 to 50°C



DCN692N - BARE UNIT DCN6901 - RETURNS SPRING KIT

18V XR METAL CONNECTOR NAILER

DCN694P2



Nail Diameter	3.4-4.0mm
Magazine Angle	33°
Nail Length	35mm
Firing Mode	Rapid Cycle™ and Sequential
Temperature Range	-20 to 50°C



DCN694N - BARE UNIT

18V XR SECOND FIX NAILER

DCN660P2

Nail Diameter	1.6mm (16Ga)
Magazine Angle	20°
Nail Length	32 - 63mm
Firing Mode	Bump & Sequential
Temperature Range	-20 to 50°C



DCN660D2 - KIT WITH 2AH BATTERIES DCN660N - BARE UNIT

18V XR BRAD NAILER

DCN680D2

Nail Diameter	1.25mm (18Ga)
Magazine Angle	0° (Straight)
Nail Length	15 - 54mm
Firing Mode	Bump & Sequential
Temperature Range	-20 to 50°C



DCN680N - BARE UNIT

18V XR NARROW CROWN STAPLER

DCN681D2

Nail Diameter	1.25mm (18Ga)
Staple Crown	5.6mm (SX staples)
Magazine Angle	0° (Straight)
Nail Length	12 - 38mm
Firing Mode	Bump & Sequential



DCN681N - BARE UNIT

18V XR FLOORING STAPLER

DCN682D2

Nail Diameter	1.25mm (18Ga)
Staple Crown	5.6mm (SX staples)
Magazine Angle	0° (Straight)
Nail Length	12 - 38mm
Firing Mode	Rapid Cycle & Sequential
Temperature Range	-20 to 50°C



DCN682N - BARE UNIT

18V XR ELECTRICIANS STAPLER

DCN701D2

Proprietary Fastener	25x17mm Crown Insulated Staples
Fuel cells required	No
LED	Yes
Shots/Charge	1200
Staple Capacity	35 (2 x 15 + 5)
Rapid Cycle	Yes
Tool Free Depth Adjust	Yes, Automatic
Cable Guide	Yes



DCN701N - BARE UNIT DRS18100-XJ - 25MM X 17MM CROWN INSULATED STAPLES (540)

18V XR 184MM MITRE SAW

DCS365M2

Blade Diameter	184 x 16mm
No Load Speed	3750rpm
Max. Cutting Capacity	250 x 50mm
Bevel Capacity	48°
Mitre Capacity	48 / 48°



DCS365N - BARE UNIT

18 XR BRUSHLESS 184MM CIRCULAR SAW

DCS570P2



Blade Diameter	184mm
No Load Speed	5500rpm
Max. Depth of Cut (90°)	64mm
Max. Depth of Cut (45°)	48mm
Bevel Capacity	57°
Hand/Arm Vibration	2.5m/s ²



DCS570N - BARE UNIT

18V XR CIRCULAR SAW

DCS391M2



Blade Diameter	165 x 20mm
No Load Speed	5150rpm
Max. Depth of Cut	55mm
Max. Depth of Cut (45°)	42.1mm
Bevel Capacity	50°
Hand/Arm Vibration	<2.5 m/s ²



DCS391N - BARE UNIT

18V XR METAL CUTTING CIRCULAR SAW

DCS373N



Blade Diameter	140 x 20mm
No Load Speed	3700rpm
Max. Depth of Cut	43mm



18V XR JIGSAW

DCS331M2



No Load stroke Rate	0 - 3000spm
Max. Depth of Cut Wood	135mm
Max. Depth of Cut Steel	10mm
Max. Depth of Cut Aluminium	25mm
Bevel Capacity	45°
Stroke Length	26mm



DCS331N - BARE UNIT

18V XR BRUSHLESS TOP HANDLE JIGSAW

DCS334P2



No Load stroke Rate	0 - 3200spm
Max. Depth of Cut Wood	135mm
Max. Depth of Cut Steel	10mm
Max. Depth of Cut Aluminium	25mm
Bevel Capacity	45°
Stroke Length	26mm
Hand/Arm Vibration - Cutting Wood	7m/s ²



DCS334N - BARE UNIT

18V XR BRUSHLESS BODY GRIP JIGSAW

DCS335N



No Load Stroke Rate	0 - 3200spm
Max. Depth of Cut Wood	135mm
Max. Depth of Cut Steel	10mm
Bevel Capacity	45°
Stroke Length	26mm
Hand/Arm Vibration - Cutting Wood	5.3m/s ²



18V XR RECIPROCATING SAW

DCS380M2



No Load Stroke Rate	0 - 2950spm
Max. Cutting Capacity Wood	300mm
Steel Sections & Pipes	100mm
PVC	100mm
Stroke Length	28.6mm



DCS380N - BARE UNIT

18V XR COMPACT RECIPROCATING SAW

DCS367N



No Load Stroke Rate	0 - 2900spm
Max. Cutting Capacity Wood	300mm
Steel Sections & Pipes	100mm
PVC	100mm
Stroke Length	28.6mm



18V XR BANDSAW

DCS371N



No Load Speed	174 Metre/min
Max. Cutting Capacity	63.5mm
Max. Watts Out	460W



18V XR PLANER

DCP580P2



No Load Speed	15000rpm
Max. Depth of Cut	2.0mm
Max. Rebating Depth	9.0mm
Planer Width	82mm



DCP580N - BARE UNIT DWV9390 - PLANER DUST BAG

18V XR OSCILLATING TOOL

DCS355M2



Oscillations per Minute	0 - 20000opm
Tool Free Accessory Fitment	Yes
Accessories Included	35



DCS355D2 - 2AH BATTERIES DCS355N - BARE UNIT

18V XR 1/4" (8MM) ROUTER, FIXED/PLUNGE BASES

DCW604NT



Power Output	930W
No Load Speed	1600 - 25500pm
Max. Cutter Diameter	30mm
Plunge Stroke Movement	55mm
Collet Size	1/4" 6-8mm
Hand/Arm Vibration	7m/s ²



18V XR 125MM RANDOM ORBIT SANDER

DCW210N



Orbits Per Minute	8,000-12,000rpm
Orbit Diameter	2.6mm
Paper Size	125mm
Fabric Dust Bag	Yes
Built-In Extractor Ports	Yes



18V XR DRYWALL CUT OUT TOOL

DCS551N



No Load Speed	26000rpm
Included Collets	3.2mm (1/8")
Max. Watts Out	550W



This product comes without a battery



18V XR THREADED ROD CUTTER

DCS350N



Speed	30spm
Mild Steel	M6, M8, M10, M12
Stainless Steel	M6, M8, M10
Cutters Included	M6, M8, M10, M12



18V XR SHEARS

DCS491N



Speed	0 - 2450spm
Max. Cutting Capacity	1.2mm
Mild Steel	1.3mm
Stainless Steel	1.3mm



18V XR CAULK GUN

DCE580N



Carrier Size	300 - 600ml
Push Force	2500N
Push Speed	51 - 333mm/min



DCE5601 - 300ML CARTRIDGE ATTACHMENT

18V XR GREASE GUN

DCGG571M1



Output Pressure	690bar, 10000PSI
Feed Rate	147g/min
Grease Type	Up To NLGI #2
Grease Capacity Bulk	453g
Cartridge	400g



18V XR BRUSHLESS STRING TRIMMER (SPLIT SHAFT)

DCM561P1S



Cutting Width/Swathe	33cm
Line Length Diameter	7.5 x 2mm
Cutting Speed	0 - 4600/0 - 6000rpm
Sound Pressure	79.5dB(A)
Sound Power	93dB(A)
Vibration	3.5m/s ²



DCM561PBS - BARE UNIT DT20658-QZ SPOOL & 2MM X 8.0M LINE DT20652-QZ LINE 2.5MM X 68.6M

DT20656-QZ CAP, SPOOL & LINE

18V XR BLOWER

DCM562P1



Blow Speed	145km/h / 90mph
Variable Speed	Yes
Lock On Switch	Yes
Sound Pressure	87B(A)
Sound Power	92.5dB(A)
Vibration	1.5m/s ²



DCM562PB - BARE UNIT

2 X 18V XR 48CM LAWNMOWER

DCMW564P2



Battery Type	2 x 18V 5.0Ah
Area of Cut Per Charge	800m ²
Metal Deck Size	51cm
Grass Collection Capacity	55L
Roller	Yes
Mulching Attachment	Yes
Cutting Heights	25-86mm
Noise Level	92dB(A)



DCMW564RN - BARE UNIT

18V XR HEDGE TRIMMER

DCM563P1



Blade Length	55.8cm
Blade strokes per min	1400
Chain Brake	< 1sec
Cutting Gap	19mm
Sound Pressure	80.5B(A)
Sound Power	98dB(A)
Vibration	2m/s ²



DCM563PB - BARE UNIT DT20666-QZ - LUBRICANT

18V XR CHAINSAW

DCM565P1



Bar Length	30cm
Chain Speed	7.7m/s
Chain Brake	< 1sec
Motor Speed	3750-4200rpm
Variable Speed	Yes
Chain Tensioning	Tool Free
Max Cutting Length	26cm
Sound Pressure	76.5dB(A)
Sound Power	96.5dB(A)
Vibration	3.5m/s ²



DCM565N - BARE UNIT DT20662-QZ OIL DT20676-QZ CHAIN DT20665-QZ CHAIN & BAR

18V XR COMPACT BLOWER

DCV100



Blow Speed	80m/s
Variable Speed	Yes
Lock On Switch	Yes
Fan Speed	0-18000rpm
Sound Pressure	85dB(A)
Sound Power	96dB(A)
Vibration	<2.5m/s ²



XR L-CLASS EXTRACTOR

DCV584L



Battery Compatibility	14.4/18/54V
Max. Airflow	15.9L/Sec
Capacity	7.5L
Wet & Dry Filter	Yes
Hose Length/Diameter	2m x 32mm
Sound Pressure	76dB(A)
Sound Power	87dB(A)



18V XR COMPACT WET & DRY VACUUM

DCV517N



Battery Compatibility	18V
Max. Airflow	15.9L/Sec
Capacity	1.9L
Wet & Dry Filter	Yes
Hose Length/Diameter	1m x 32mm
Sound Pressure	76dB(A)
Sound Power	87dB(A)



18V XR COMPACT RADIO

DCR020



Battery Compatibility	12/14.4/18V
Power Source	AC/DC
Modes	DAB(+)/FM/AUX/USB
USB Charger	5V/2.1A
AUX Input	3.5mm



12V/18V/54V BLUETOOTH SPEAKER

DCR011



Battery Compatibility	12/18/54V
Sound Pressure Level	SPL > 97dB @1m
High Signal-to-Noise Ratio	80dB SNR
Impedance	6 Ohms
Audio Output Power	10Watts
Audio/video/remote control profile (AVRCP)	Yes
2.1Amp USB Charging Port	Yes
2 x 76mm Speakers	
Base Port	Yes
Size	255x140x183mm



BLUETOOTH ADAPTOR

DCR002



Connection Type	3.5mm
-----------------	-------



18V XR COMPACT LED PIVOT LIGHT

DCL040



Output	110 Lumen
Battery Pattern	2 Zone
Light Settings	1
Pivoting Head	Yes



18V XR LED SPOT LIGHT

DCL043



Output	120 - 1000 Lumen
Beam Pattern	Area - 180°
Light Settings	2
IP Rating	IP54
Pivoting Head	Yes



18V XR LED PIVOT LIGHT

DCL050



Output	250 - 500 Lumen
Beam Pattern	Area - 180°
Light Settings	2
IP Rating	IP54
Pivoting Head	Yes



18V XR LED AREA LIGHT

DCL060



Output	1500 Lumen
Beam Pattern	Area
Light Settings	2
Pivoting Head	Yes



18V XR LED TRIPOD LIGHT

DCL079



Light output	1000lm, 1800lm, 3000lm
IP Rating	IP55
Max. Runtime	15.6 hours
Beam Pattern	Area - 180°
Light Settings	3
Pivoting Head	Yes



18V XR INFLATOR

DCC018N



Voltage Adaptor	12V
Max. Pressure	11bar
Power Supply	12V/240V/18V
Air Flow	High & Low Pressure
Output	0.35l/min@6.2 bar, 0.6l/min@2 bar
Deflate Function	Yes
Gauge Display	Digital x 2
Auto Stop	Yes (High Pressure)
Maximum Pressure	11bar/160psi
Gauge Accuracy	+/- 0.15bar



18V XR 4AH BATTERY

DCB182



Battery Capacity	4.0Ah
Tool Connect Compatible	No



18V XR 5AH BATTERY

DCB184



Battery Capacity	5.0Ah
Tool Connect Compatible	No



18V 4AH COMPACT BATTERY

DCB189



Battery Capacity	4Ah
Tool Connect Compatible	No



18V XR 2AH BATTERY

DCB183



Battery Capacity	2Ah
Tool Connect Compatible	No



18V XR 12V CAR CHARGER

DCB119



Battery	Li-Ion
Charging Current	2.5A
Charging Time	40-90 min



18V XR 240V CHARGER

DCB115



Battery	XR Li-Ion
Charging Current	4.0A
Charging Time	(2Ah) 30min




18V XR USB CHARGER

DCB090



Voltage	12V, 14.4V, 18V
Battery	Li-Ion
Charging Current	1.5A



18V XR COMPACT TWIN PACK

DCK2062M2T



Kit Includes:
 DCD709 18V XR Brushless Compact Hammer Drill Driver
 DCF809 18V XR Brushless Ultra Compact Impact Driver



18V XR COMPACT TWIN KIT

DCK266P2



Kit Includes:
 DCD796 2 Speed Combi Drill
 DCF887 Impact Driver
 DCB184 2 x 5Ah Batteries
 DCB115 240V Charger
 ODS150 Toughsystem™ Kitbox



DCK266D2 - 2AH BATTERIES

18V XR PREMIUM TWIN KIT

DCK276P2



- Kit Includes:
 DCD996 XRP 3 Speed Combi Drill
 DCF887 Impact Driver
 DCB184 2 x 5Ah Batteries
 DCB115 240V Charger
 DS150 Toughsystem™ Kitbox



18V XR BRUSHLESS 5 AH 2 TOUGHSYSTEM™

18V XR SDS TWIN KIT

DCK229P2T



- Kit Includes:
 DCD996 XRP 3 Speed Combi Drill
 DCH273 3 Mode SDS Hammer Drill
 DCB184 2 x 5Ah Batteries
 DCB115 240V Charger
 DWST1-71195 TSTAK™ VI Kitbox



18V XR BRUSHLESS 5 AH 2 TSTAK™

18V XR SIX KIT

DCK694P3



- Kit Includes:
 DCD996 XRP 3 Speed Combi Drill
 DCF887 Impact Driver
 DCS391 Circular Saw
 DCG412 Grinder
 DCS331 Jigsaw
 DCL040 LED Pivot Light
 DCB182 3 x 5Ah Batteries
 DCB115 240V Charger
 DS300 2 x Toughsystem™ Kitbox



18V XR BRUSHLESS 5 AH 3 TOUGHSYSTEM™

18V XR SIX KIT

DCK665P3T



- Kit Includes:
 DCD796 2 Speed Combi Drill
 DCS355 Oscillating Tool
 DCP580 Planer
 DWV9390 Planer Bag
 DCS391 Circular Saw
 DCS331 Jigsaw
 DCL050 LED Pivot Light
 DCB182 3 x 5Ah Batteries
 DCB115 240V Charger
 DWST1-71195 2 x TSTAK™ VI Kitbox



18V XR BRUSHLESS 5 AH 3 TSTAK™

18V XR BRUSHLESS COMPACT 6 PIECE KIT**DCK623P3**

Kit Includes:

DCG405	18V XR 125mm Small Angle Grinder
DCS367	18V XR Compact Reciprocating Saw
DCS570	18V XR 184mm Circular Saw
DCF887	18V XR 3-Speed Impact Driver
DCD796	18V XR Compact Hammer Drill Driver
DCL050	18V XR Handheld LED Area Light
1-70-322 x 2	Toughsystem™ DS300
DCB184 x 3	18V XR 5.0Ah Batteries
DCB115	XR Multi-Voltage Charger

