



METALWORKING & CONCRETE

Offering durability, ergonomics and power while taking into account the user's health with the Perform & Protect system. All tools are built for maximum toughness against metal and concrete.

www.DEWALT.co.uk

115MM ANGLE GRINDER

DWE4206

Power Input	1010W
No Load Speed	11000rpm
Max. Disc Diameter	115mm
Vibration	8.3m/s ²



DWE4206K - INCLUDES KITBOX AVAILABLE IN 110V & 240V

230MM ANGLE GRINDER

DWE490

Power Input	2000W
No Load Speed	6600rpm
Max. Disc Diameter	230mm
Vibration	7.1m/s ²



AVAILABLE IN 240V

230MM ANGLE GRINDER

DWE492K

Power Input	2200W
No Load Speed	6600rpm
Max. Disc Diameter	230mm
Vibration	7.1m/s ²



AVAILABLE IN 110V & 240V



POLISHER

DWP849X

Power Input	1250W
No Load Speed	0 - 600/3500rpm
Max. Disc Diameter	230mm
Vibration	2.3m/s ²



AVAILABLE IN 240V

2300W 355MM ABRASIVE METAL CUTTING CHOP SAW

D28730

Power Input	2300W
No Load Speed	4000rpm
Disc Diameter	355mm
Max. Cutting Capacity Rectangular	115 x 130mm
Max Cutting Capacity at 90° Square	115 x 115mm
Max Cutting Capacity at 90° L-Shaped	137 x 137mm
Max Cutting Capacity at 90° Round	130mm
Max Cutting Capacity at 45° Rectangular	95 x 105mm
Max Cutting Capacity at 45° Square	98 x 98mm
Max Cutting Capacity at 45° L-Shaped	110 x 110mm
Max Cutting Capacity at 45° Round	105mm



AVAILABLE IN 110V & 240V

TCT CHOP SAW
DW872

Power Input	2200W
No Load Speed	1300rpm
Disc Diameter	355mm
Max. Cutting Capacity Square Profile	100 x 100mm
Max Cutting Capacity at 90° Rectangular	75 x 130mm
Max Cutting Capacity at 90° L-Shaped	92 x 92mm
Max Cutting Capacity at 90° Round	130mm
Max Cutting Capacity at 45° Rectangular	79 x 123mm
Max Cutting Capacity at 45° Square	79 x 79mm
Max Cutting Capacity at 45° L-Shaped	56 x 56mm
Max Cutting Capacity at 45° Round	79mm


AVAILABLE IN 110V & 240V
TILE SAW
D24000

Power Input	1600W
No Load Speed	4200rpm
Disc Diameter	250mm
Vibration	<2.5m/s ²
Max. Cutting Capacity	610mm
Max. Depth of Cut	95mm

D240001 Leg Stand also available.


AVAILABLE IN 110V & 240V